


# AirDIV Poly 3

|                     |                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Composition:</b> | 100 % polyester<br>Endless fibers (multifilament) with<br>inwrought carbonic fiber (less than 1 %)<br>and special anti-flammability treatment |
| <b>Coating:</b>     | 1x polyurethane                                                                                                                               |
| <b>Colour:</b>      | Dark grey                                                                                                                                     |



---

|                    |                                                                                                                                 |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Properties:</b> | Fire resistant<br>Antibacterial (EN 20645)<br>Antistatic<br>Impermeable<br>Machine washable<br>High strength<br>Ozone cleanable |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------|

---

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| <b>Weight:</b>                 | 202 ± 20,2 g/m <sup>2</sup> (EN 12127)                               |
| <b>Thickness:</b>              | 0,3 mm                                                               |
| <b>Warp/Weft strength:</b>     | 1800/1100 ± 90/55 N (EN 13934-1)                                     |
| <b>Washing shrinkage:</b>      | - 0,5 / 0,0 ± 0,1 % EN ISO 6330, warp/weft, 40 °C                    |
| <b>Permeability:</b>           | 0 + 5 m <sup>3</sup> /h/m <sup>2</sup> by 120 Pa                     |
| <b>Fire resistance:</b>        | HL 3 according to EN 45545-2 for R1 material<br>NFPA 130<br>ECE R118 |
| <b>Temperature resistance:</b> | - 40 to + 110 °C                                                     |

---

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Maintenance:</b> |      |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|